Nuclear Regulatory Commission

maintain confinement of radioactive material under normal, off-normal, and credible accident conditions.

- (m) To the extent practicable in the design of spent fuel storage casks, consideration should be given to compatibility with removal of the stored spent fuel from a reactor site, transportation, and ultimate disposition by the Department of Energy.
- (n) Safeguards Information shall be protected against unauthorized disclosure in accordance with the requirements of §73.21 and the requirements of §73.22 or §73.23 of this chapter, as applicable

 $[64\ {\rm FR}\ 56126,\ {\rm Oct.}\ 15,\ 1999,\ {\rm as}\ {\rm amended}\ {\rm at}\ 65\ {\rm FR}\ 50617,\ {\rm Aug.}\ 21,\ 2000;\ 73\ {\rm FR}\ 63573,\ {\rm Oct.}\ 24,\ 2008;\ 76\ {\rm FR}\ 8891,\ {\rm Feb.}\ 16,\ 2011]$

§ 72.238 Issuance of an NRC Certificate of Compliance.

A Certificate of Compliance for a cask model will be issued by NRC for a term not to exceed 40 years on a finding that the requirements in §72.236(a) through (i) are met.

[76 FR 8891, Feb. 16, 2011]

§ 72.240 Conditions for spent fuel storage cask renewal.

- (a) The certificate holder may apply for renewal of the design of a spent fuel storage cask for a term not to exceed 40 years. In the event that the certificate holder does not apply for a cask design renewal, any licensee using a spent fuel storage cask, a representative of such licensee, or another certificate holder may apply for a renewal of that cask design for a term not to exceed 40 years.
- (b) The application for renewal of the design of a spent fuel storage cask must be submitted not less than 30 days before the expiration date of the CoC. When the applicant has submitted a timely application for renewal, the existing CoC will not expire until the application for renewal has been determined by the NRC.
- (c) The application must be accompanied by a safety analysis report (SAR). The SAR must include the following:
- (1) Design bases information as documented in the most recently updated final safety analysis report (FSAR) as required by §72.248;

- (2) Time-limited aging analyses that demonstrate that structures, systems, and components important to safety will continue to perform their intended function for the requested period of extended operation; and
- (3) A description of the AMP for management of issues associated with aging that could adversely affect structures, systems, and components important to safety.
- (d) The design of a spent fuel storage cask will be renewed if the conditions in subpart G of this part and §72.238 are met, and the application includes a demonstration that the storage of spent fuel has not, in a significant manner, adversely affected structures, systems, and components important to safety.
- (e) In approving the renewal of the design of a spent fuel storage cask, the NRC may revise the CoC to include terms, conditions, and specifications that will ensure the safe operation of the cask during the renewal term, including but not limited to, terms, conditions, and specifications that will require the implementation of an AMP.

[76 FR 8891, Feb. 16, 2011]

§72.242 Recordkeeping and reports.

- (a) Each certificate holder or applicant shall maintain any records and produce any reports that may be required by the conditions of the CoC or by the rules, regulations, and orders of the NRC in effectuating the purposes of the Act.
- (b) Records that are required by the regulations in this part or by conditions of the CoC must be maintained for the period specified by the appropriate regulation or the CoC conditions. If a retention period is not specified, the records must be maintained until the NRC terminates the CoC.
- (c) Any record maintained under this part may be either the original or a reproduced copy by any state-of-the-art method provided that any reproduced copy is duly authenticated by authorized personnel and is capable of producing a clear and legible copy after storage for the period specified by NRC regulations.
- (d) Each certificate holder shall submit a written report to the NRC within